

Temperature Sensor

Featuring LoRaWAN®

ATS30x

◆ Introduction

ATS30x is an advanced resistance temperature sensor with a visualized data display. It features extendable connecting lines and a diverse range of detecting probes, including A-class, B-class, and A-class food-grade temperature probes. Moreover, it provides the option for a magnetic contact switch sensor. ATS30x prioritizes security and reliability, ensuring traceable data and effortless data exports for seamless integration.

ATS30x is designed for measuring a wide range of temperature in harsh environments and transmitting data using LoRaWAN® technology. With this low power consumption technology, ATS30x can maintain a long operational life with its embedded batteries. Combining with LoRaWAN® gateway and IoT Cloud solution, users can manage all sensor data remotely and visually.

ATS30x is widely used for temperature monitoring applications like food processing, cold chain storage of food or medicine, etc.



ATS301



ATS302

◆ Features

- Provide optional five types of high-accuracy PT100 temperature probes and one magnetic contact switch sensor
- IP65 waterproof enclosure with dust plug, suitable for harsh environment
- Support automated temperature monitoring and anti-tamper recording of data in compliance with HACCP, meeting the authenticity requirements of 21 CFR Part 11B electronic record
- EN12830 certified for cold-chain applications
- Provide simplified PDF data export for easy documentation without complex paperwork
- Built-in two large-capacity replaceable batteries, ensuring an extended battery life
- Features low-consumption LCD display, enabling intuitive data reading
- Store up to 10,000 historical records locally and supports retransmission to prevent data loss
- Equipped with NFC and Type-C USB for quick and easy configuration
- Function effectively with standard LoRaWAN® gateways and network servers
- Compatible with IoT Cloud and Development Platform

◆ Specifications

Wireless Transmission

Technology	LoRaWAN®
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923-1&2&3&4
Tx Power	16dBm (868MHz)/22dBm (915MHz)/19dBm (470MHz)
Sensitivity	-137dBm @300bps
Mode	OTAA/ABP Class A

Sensor Connector

Connector Type	5-pin M12 A-Coded Male Connector
Connector Number ¹	ATS301: 1 × Connector for PT100 Probe or Magnet Switch Sensor ATS302: 2 × Connectors for two PT100 Probes or PT100 + Magnet Switch Sensor
PT100 Connection	3-wire Connection

Display

Display	LCD Segment Code Screen
Viewing Direction	12 O'clock

Others

Button	1 × External Power Button + 1 × Internal Reset Button
LED Indicator	1 × Status Indicator (Internal)

Configuration	Mobile App (via NFC) or PC software (via USB Type-C)
Data Logging	10, 000 measurements and supports to export as CSV or PDF file
Physical Characteristics	
Power Supply	2 × 4000 mAh ER18505 Li-SOCl ₂ Batteries or Type-C USB (5V/1A)
Battery Life ² (30°C, 10 min interval)	ATS30x + One or Two PT100 Probes: Around 5 years ATS302 + PT100 Probe + Magnet Sensor: Around 5 years (10 triggers per day) ATS30x + One Magnet Sensor: Over 10 years (10 triggers per day)
Operating Temperature	-30°C to +70°C
Relative Humidity	0% to 95% (non-condensing)
Ingress Protection	IP65
Weight	175 g (TS301), 185 g (TS302)
Dimension	109.35 × 75 × 29 mm (4.31 × 2.95 × 1.14 in)
Installation	Wall Screw Mounting, Magnetic Mounting (Opt.)
Approvals	
Regulatory	CE, FCC, EN12830
Environmental	RoHS

¹ATS302 does not support to connect both magnet switch sensors.

²Tested under laboratory conditions and for guideline purposes only.

Optional Sensors

PT100 Probes*					
Model	B05-125-200	AF10-125-150	A03-050-150	A05-500-150	A09-085-200-B046
Measuring Range	-40 °C ~ 125 °C		-200 °C ~ 50 °C	-50 °C ~ 500 °C	-20°C ~ 85°C
Measuring Accuracy	± 0.5°C (-40°C~40°C), ± 1°C (40°C~125°C)	± 0.4°C	± 0.5°C (-175°C~50°C) , ± 0.55°C (-200°C~-175°C)	± 0.5°C	± 0.4°C
Measuring Resolution	0.1°C				
Probe Type	Straight tube,	Needle, Food	Straight tube, 304 Stainless		Straight tube

	304 Stainless Steel	Grade 316 Stainless Steel	Steel		(with Baffle), 304 Stainless Steel (Baffle Dimension: 46*14mm)
Probe Length	Φ4*50 mm	Φ4*100 mm	Φ4*30 mm		Φ4.8*90 mm
Cable Length	2 m	1.5 m			2m
Cable Material	PVC	Food Grade Silicone	Teflon	Fiberglass	PVC
Cable Operating Temperature	-30 °C~105 °C	-60 °C~250 °C	-200 °C~290 °C		-20 °C~85 °C
Ingress Protection	IP67			IP30	IP67
Magnet Switch Sensor					
Detection Distance	20-30 mm				
Cable Length	1.5 m				
Dimension	32 × 15 × 8 mm (1.25 × 0.59 × 0.31 in)				
Installation	Wall Screw Mounting, 3M Tape Mounting				

* Please contact us for customized probe options according to your specific requirements.

◆ Dimension(mm)

